

## Rendex® Patch

Based on available information, not classified as hazardous according to criteria of NOHSC. Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** Rendex® Patch

**Product Code(s):** RR-PATCH

**Supplier:** Prestige Wall Systems Pty Ltd trading as Prestige Wall Systems

**ABN:** 97 157 346 486

**Street Address:** 24 Humphries Tce, Kilkenny SA 5009

**Telephone Number:** +61 8 8244 1999

**Facsimile Number:** 1300 676 233

**Emergency Number:** 1300 663 118 (all hours)

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Product Description:** Surface Coating. Applied by brush, roller or spray. Coloured viscous liquid.

Components	CAS Number	Proportion	Risk Phrases
Pigments	-	0 - 30%	-
Synthetic Polymer(s)	-	10 - 50%	-
Sand (Crystalline silica)	14808-60-7	20 - 80%	R48/20, Carc. Cat.1 R49
Water	7732-18-5	10 - 40%	-
Propylene Glycol	57-55-6	1 - <10%	-
Ingredients determined not to be hazardous	-	to 100%	-

### 3. HAZARDS IDENTIFICATION

Poisons Schedule: None allocated.

### 4. FIRST AID MEASURES

<b>Inhalation</b>	Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
<b>Skin Contact</b>	If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
<b>Eye Contact</b>	If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.
<b>Ingestion</b>	Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical assistance.

**Notes to physician:** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

<b>Specific Hazards:</b>	Non-combustible material.
<b>Fire-fighting advice:</b>	Non-combustible material, however, following evaporation of the water component of the material, the residual material can burn if ignited. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if at risk of exposure to vapour or products of combustion.
<b>Suitable Extinguishing Media:</b>	Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

## 7. HANDLING AND STORAGE

<b>Handling advice</b>	Avoid eye contact and repeated or prolonged skin contact.
<b>Storage advice</b>	Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational Exposure Limits</b>	No value assigned for this specific material by the National Occupational Health and Safety Commission.
<b>Engineering Control Measures</b>	Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.
<b>Personal Protective Equipment</b>	Overalls, Safety Shoes, Safety Glasses, Gloves, Respirator.

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Avoid breathing dust when sanding. Wet sand or use a dust mask. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Viscous liquid	<b>% Volatile by Volume</b>	Not Available
<b>Colour</b>	Coloured	<b>Solubility in water (g/L)</b>	Miscible
<b>Solubility</b>	Miscible with water	<b>Melting Point/Range (°C)</b>	Not Applicable
<b>Specific Gravity</b>	1-1.9 @20°C	<b>Boiling Point/Range (°C)</b>	100 (water)
<b>Relative Vapour Density (air=1)</b>	>1	<b>Decomposition Point (°C)</b>	Not Available
<b>Vapour Pressure (20 °C)</b>	Not Available	<b>pH</b>	8-10
<b>Flash Point (°C)</b>	Not Applicable	<b>Viscosity</b>	Not Available
<b>Flammability Limits (%)</b>	Not Applicable	<b>Evaporation Rate</b>	Not Available
<b>Autoignition Temperature (°C)</b>	Not Applicable		

## 10. STABILITY AND REACTIVITY

Stability: No information available.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion</b>	No adverse effects expected, however large amounts may cause nausea and vomiting.
<b>Eye Contact</b>	May be an eye irritant.
<b>Skin Contact</b>	Contact with skin may result in irritation.
<b>Inhalation</b>	Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea. Breathing in mists or aerosols may produce respiratory irritation.
<b>Long Term Effects</b>	No information is available for the product. Repeated or prolonged breathing of silica dust may result in chronic lung diseases such as silicosis and potentially lung cancer. However, due to the particle size of the silica (sand) this is not expected to be relevant providing this product is used as recommended and good occupational work practices are observed.
<b>Toxicological Data</b>	No LD50 data available for the product.

The components in the proportions present are not considered to present a hazard under conditions of good occupational work practice.

## 12. ECOTOXICOLOGICAL INFORMATION

Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

## 14. TRANSPORT INFORMATION

<b>Road and Rail Transport</b>	Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.
<b>Marine Transport</b>	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
<b>Air Transport</b>	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. REGULATORY INFORMATION

<b>Classification</b>	Based on available information, not classified as hazardous according to criteria of NOHSC.
<b>Poisons Schedule</b>	None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

This Safety Data Sheet has been prepared by Prestige Wall Systems Technical Department.

Reason(s) for Issue:

### Review of Content

- This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Prestige Wall Systems cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.
- If clarification or further information is needed, the user should contact Prestige Wall Systems using the contact details on page 1.
- Prestige Wall Systems responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.